

## Series KLT11D



# Thermostat KLT11D


FTPT02-004I\_121001



### FEATURES:

- Cooling or heating control.
- One input probe.
- Probe type NTC or PTC selectable by parameter.
- Output to one SPDT relay.
- Static defrosting.
- Temperature limit on display during defrosting.
- Error indication and fault function: 50 % cycle.
- Easy access to parameters by code.
- Input for parameter-programming device KLKEY.

### HOW TO ORDER:



Options: Ask to factory

### AVAILABLE MODELS:

- KLT11D-R230C
- KLT11D-R110C
- KLT11D-R12C
- KLT11D-R24C

### SPECIFICATIONS:

#### Panel mounting

Cutout: 71 x 29 mm (2.79 x 1.14 inch)

#### Dimensions

Front: 76,5 x 36 mm (3.01 x 1.41 inch)

Depth: 62 mm (2.44 inch)

#### Measurement range

-50°C to 150°C / -58°F to 302°F

#### Accuracy

Better than 1% of full scale

#### Resolution

1°

#### Probe

PTC (1000 Ohms, 25°C) / NTC

#### Output

SPDT Relay Resistive load 16A

1HP 240Vac -- 10FLA, 60LRA 240Vac

#### IP Protection

Front: IP64

Rear: IP20

### WIRING CONNECTIONS:

