KELD | DRIVES — FARM

FARM1010 / FARM1012

Mounted Wall Drive

for EC Motors



Three Phase
IM, PM, BLDC, SynRM

>95% efficiency
at nominal power

2.2 kW	IP66	190–480 Vac
3.0 HP	Aluminum enclosure	Three Phase
POWER OUTPUT	PROTECTION	VOLTAGE RANGE

CORE FEATURES

- Vectorial FOC Algorithm · Sensorless control
- Sinusoidal output · Natural cooling
- Designed for very hard environments
- Surge protection module
- External Alarm blinking LED

INPUTS & OUTPUTS

- Alarm Relay + Configurable Aux. Relay
- Start / Stop Input + Aux.
- 0–10 V / 10–0 V Speed Regulation / 4–20 mA
- Motor Temp. Sensor (Clixon)

PROTECTIONS

Supply/Input

- Under/Overvoltage Protection
- Inrush-Current Protection

Motor/Output

- Short-Circuit Protection
- Overload Protection
- Locked-Rotor Protection
- Phase-Loss Protection

Internal

- Overtemperature Protection

COMMUNICATIONS

Modbus RS-485
RTU protocol

TECHNICAL SPECIFICATIONS

Output Voltage

FARM1010	FARM1012
0–430 Vac, 3-phase (Electrolytic capacitor)	0–370 Vac, 3-phase (MKP capacitor)

Dimensions	220 x 215 x 165 mm
Mounting	Wall Mount
IP Protection	IP66
Power Supply	Three Phase 190–480 Vac (±20%), 50/60 Hz
Power Factor	No active PFC
Power Output	2.2 kW / 3.0 HP
Output Frequency	0–400 Hz
Output Current	8.0 Arms
Approvals	CE · UL · RoHS
Humidity	0–95% (non-condensing)
Altitude	2000 m (derate above 1000 m: 1%/100 m)
Operating Temp.	10°C to 50°C (Tj >40°C derating)
Storage Temp.	-40°C to 70°C

© 2026 Electrónica KELD S.L. All rights reserved. Specifications are subject to change without notice. KELD cannot be held liable for errors in printed material and reserves the right to alter its products without notice.

Polígono Empresarium · C/Lentisco, 15 · 50720 La Cartuja Baja · Zaragoza (Spain)
+34 976 429 099 · keld@keld.es