KELD

HVAC - ACCESORIES - KLKEY

Parameter Programming Key

KLKEY

CE



BATTERY POWERED
12V 23A
POWER

LOAD / COPY
Parameter transfer
FUNCTION

LED STATUS
Error indication
STATUS

CORE FEATURES

- Battery-powered parameter programming key
- Loads parameter sets from a controller
- Copies parameter sets to controllers of the same type
- Micro-switch function selection
- Low battery, communication error and controller type error indication

TECHNICAL SPECIFICATIONS

Dimensions	56 × 36 × 16 mm (2.20 × 1.42 × 0.63 inch)
Operating Temp.	0°C to 50°C (32 to 122°F)
Storage Temp.	-20°C to 70°C (-4 to 158°F)
Battery	12V, type 23A

FUNCTION

- Load parameters from controller to KLKEY
- Copy parameters from KLKEY to controller
- Controller must not be powered during copying
- Power for copying is supplied by KLKEY itself

HOW TO ORDER

Reference: KLKEY

Ask to factory

STATUS INDICATIONS

- **GREEN** 🟢
  - Solid : Successful operation
  - Flashing : Low battery
- **RED** 🔴
  - Flashing: Communication or memory error
- **ALTERNATING** 🟢🔴
  - Controller type mismatch

Polígono Empresarium · C/Lentisco, 15 · 50720 La Cartuja Baja · Zaragoza (Spain)
+34 976 429 099 · keld@keld.es

www.keld.es