
KELD | DRIVES — KMD SERIES

KMD1-0000GVG

Mounted Wall Drive

for EC Motors



Single Phase
IM, PM, BLDC, SynRM

>94% efficiency
at 400V / 1 kW

1.0 kW	IP66	90–265 Vac
1.35 HP	Aluminum enclosure	Single Phase
POWER OUTPUT	PROTECTION	VOLTAGE RANGE

CORE FEATURES

- Vectorial FOC Algorithm · Sensorless control
- Sinusoidal output · Natural cooling
- Designed for very hard environments
- Replaceable surge protection module

External Alarm multi-color LED
Customizable logo and housing
KMD APP available on the App Store (iOS) and Google Play (Android)

INPUTS & OUTPUTS

- Alarm Relay + Configurable Aux. Relay
- Start / Stop Input + Configurable Aux. input
- 0–10 V / 10–0 V Speed Regulation
- Motor Temp. Sensor (Pt100 / PTC / Clixon)

PROTECTIONS

Supply/Input
- Under/Overvoltage Protection
- Inrush-Current Protection

Motor/Output
- Short-Circuit Protection
- Overload Protection
- Locked-Rotor Protection
- Phase-Loss Protection

Internal
- Overtemperature Protection

TECHNICAL SPECIFICATIONS

Output Voltage

KMD1-0000GVG
0–265 Vac, 3-phase

Dimensions	210 x 236 x 137 mm
Mounting	Wall Mount
IP Protection	IP66
Power Supply	Single Phase 90–265 Vac 50/60 Hz
Power Factor	>99% (Active PFC)
Power Output	1.0 kW / 1.35 HP
Output Frequency	0–400 Hz
Output Current	5 Arms
Safety / EMC	EN 61800-5-1 · EN 61800-3
Approvals	CE · RoHS
Humidity	10–90% (non-condensing)
Operating Temp.	-20°C to 40°C (derating >40°C)
Storage Temp.	-40°C to 60°C
Altitude	2000 m max. (derate >1000m: 1%/100m)

COMMUNICATIONS

Modbus RS-485	USB	Bluetooth	Optional BACnet
RTU protocol	Firmware Upgrade		

© 2026 Electrónica KELD S.L. All rights reserved. Specifications are subject to change without notice. KELD cannot be held liable for errors in printed material and reserves the right to alter its products without notice.

Polígono Empresarium · C/Lentisco, 15 · 50720 La Cartuja Baja · Zaragoza (Spain)
+34 976 429 099 · keld@keld.es

www.keld.es