KELD | DRIVES — STARK

KMDF1L08A5A

Mounted Wall Drive

for EC Motors



Single Phase
IM, PM, BLDC, SynRM

>95% efficiency
at 230V / 2.2 kW

2.2 kW	IP55	90–265 Vac
3.0 HP	Aluminum enclosure	Single Phase
POWER OUTPUT	PROTECTION	VOLTAGE RANGE

CORE FEATURES

- Vectorial FOC Algorithm · Sensorless control
- Sinusoidal output
- IP55 enclosure · Natural cooling (motor mount) or forced (ventilation kit)
- Designed for very hard environments
- External Alarm blinking LED
- Integrated LCD control panel with F1/F2 preset programs

INPUTS & OUTPUTS

- Alarm Relay + Configurable Aux. Relay
- Start / Stop Input + Configurable Aux. input
- 0–10 V / 10–0 V Speed Regulation / 4–20 mA
- Motor Temp. Sensor (Pt100 / PTC / Clixon)

PROTECTIONS

Supply/Input

- Under/Overvoltage Protection
- Inrush-Current Protection

Motor/Output

- Short-Circuit Protection
- Overload Protection
- Locked-Rotor Protection
- Phase-Loss Protection

Internal

- Overtemperature Protection

COMMUNICATIONS

Modbus RS-485
RTU protocol

TECHNICAL SPECIFICATIONS

Output Voltage

KMDF1L08A5A
0–265 Vac, 3-phase

Dimensions	264 x 170 x 135 mm
Mounting	Wall Mount (ventilation kit)
IP Protection	IP55
Power Supply	Single Phase 200–240 Vac (±10%), 50/60 Hz
Power Factor	>99% (Active PFC)
Power Output	2.2 kW / 3.0 HP
Output Frequency	0–400 Hz
Output Current	8.4 Arms
Approvals	CE · RoHS
Humidity	0–95% (non-condensing)
Altitude	2000 m (derate above 1000 m: 1%/100 m)
Operating Temp.	-10°C to 40°C (Tj >40°C derating)
Storage Temp.	-40°C to 70°C

VENTILATION KIT

KMD-VENTKIT
Wall mounting accessory

- Optional accessory for wall mounting
- Incorporates forced-air cooling fan
- Required when motor cooling is insufficient

© 2026 Electrónica KELD S.L. All rights reserved. Specifications are subject to change without notice. KELD cannot be held liable for errors in printed material and reserves the right to alter its products without notice.

Polígono Empresarium · C/Lentisco, 15 · 50720 La Cartuja Baja · Zaragoza (Spain)
+34 976 429 099 · keld@keld.es